

# advantage range CRH304

## 4-piston radial mount caliper

### Part numbers and handing

Disc Thickness	Position	Ø38.1 / 41.3 pistons	Ø31.8 / 31.8 pistons
25.4 -28mm	LH trailing	CRH304/28-38/41LT	CRH304/28-32/32LT
	RH trailing	CRH304/28-38/41RT	CRH304/28-32/32RT
	LH leading	CRH304/28-38/41LL	CRH304/28-32/32LL
	RH leading	CRH304/28-38/41RL	CRH304/28-32/32RL



### Applications

Rally Rear, Single Seater, Saloon Car Rear, Hill Climb.

### Replacement parts

Item	Ø38.1 / 41.3 pistons	Ø31.8 / 31.8 pistons
Seal Kit, axle set	CSK3841E900	CSK3232E900
Pistons, ALUMINIUM (each)	PAS4438X551 PAS4441X551	PAS4471X741
Pistons, STAINLESS STEEL (each)	PSS3828X600 PSS4128X600	PSS3228X600
AKB Springs (each)	SSC3435X608	
Bridge Pipe (each)	PSC4463X653	
Bleed Screw (each)	FSB0080X008	
Inlet Adapter, 3/8 UNF male to male	FSA3435X630	
Copper gasket	FCG0080X015	

### Key features and benefits

- Radial mount for maximum rigidity and firm, consistent pedal.
- Aluminium pistons as standard, stainless steel pistons available as an option to reduce heat transfer to brake fluid.
- 2Kg Anti-knock back springs.
- Remove pad retainer bolt and sleeve to change pads.
- Stainless steel fluid transfer pipe.

### Specifications

- Disc diameter range: ø250 - 304mm.
- Disc thickness range: 25.4 - 28mm.
- Fluid inlet 3/8"-24 UNF (-3) male.
- Dry weight 1.9kg excluding pads.
- Alcon pad reference: 4463/39 area 80cm<sup>2</sup> per caliper, 4463/42 area 92cm<sup>2</sup> per caliper, 16mm thick, 113.5mm long.

### Installation dimensions

