



# advantage range **CLH304**

## 4-piston lug mount H-type caliper

### Part numbers and handing

| Disc thickness | Position    | Ø38.1/41.3 pistons |
|----------------|-------------|--------------------|
| 22.9 - 25.4    | LH trailing | CLH304/25-38/41LT  |
|                | RH trailing | CLH304/25-38/41RT  |
|                | LH leading  | CLH304/25-38/41LL  |
|                | RH leading  | CLH304/25-38/41RL  |

### Replacement parts

| Item                                | Ø38.1/41.3 pistons         |
|-------------------------------------|----------------------------|
| Seal Kit, axle set                  | CSK3841E900                |
| Pistons, ALUMINIUM, each            | PAS4438X551<br>PAS4441X551 |
| Pistons, STAINLESS STEEL, each      | PSS3828X600<br>PSS4128X600 |
| AKB Springs, each                   | SSC3435X609                |
| Bridge Pipe (each)                  | PSC4463X652                |
| Bleed Screw, each                   | FSB0080X008                |
| Inlet Adapter, 3/8 UNF male to male | FSA3435X630                |
| Copper gasket                       | FCG0080X015                |

### Applications:

Rally rear, Single seater, Saloon car rear, Hill climb



### Key features and benefits

- Supplied with lugs un-machined so customers can machine their own mounting holes within the limits specified below
- Aluminium pistons as standard, stainless steel pistons available as an option to reduce heat transfer to brake fluid
- 2Kg Anti-knock back springs
- Remove pad retainer bolt and sleeve to change pads
- Stainless steel fluid transfer pipe

### Specifications

- Disc diameter range: Ø250 to 304mm.
- Disc thickness range: 22.9 to 25.4mm.
- Fluid inlet 3/8-24 UNF (-3) female.
- Dry weight 2.2kg excluding pads.
- Alcon pad reference: 4463/39 area 80cm² per caliper, 4463/42 area 92cm² per caliper, 16mm thick, 113.5mm long.

### Installation dimensions

